

Safety Data Sheet

Copyright, 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 27-8119-3
 Version number:
 15.00

 Revision date:
 20/02/2020
 Supersedes date:
 13/08/2019

Transportation version number: 4.00 (15/02/2018)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 80349 Perfect-It III Extra Fine PLUS

Product Identification Numbers

GC-8010-4166-3 GC-8010-4167-1 UU-0016-6331-7 UU-0016-6335-8

7000084862 7000034473 7100057580 7100064019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Notes on labelling

H304 is not required on the label due to the product's viscosity

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH	% by Wt	Classification
			Registration No.		
Non-Hazardous Ingredients	Mixture			50 - 70	Substance not classified as hazardous
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		926-141-6	01- 2119456620- 43	15 - 40	Asp. Tox. 1, H304; EUH066
Aluminium Oxide (non-fibrous)	1344-28-1	215-691-6		5 - 10	Substance with a Community level exposure limit in the workplace
White mineral oil (petroleum)	8042-47-5	232-455-8	01- 2119487078- 27	1 - 5	Asp. Tox. 1, H304
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics		920-107-4	01- 2119453414- 43	1 - 5	Asp. Tox. 1, H304; EUH066
1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9		< 0.05	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=10

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide.
Irritant vapours or gases.

Condition

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

IngredientCAS NbrAgencyLimit typeAdditional commentsAluminium Oxide (non-fibrous)1344-28-1UK HSCTWA(as inhalable dust):10

mg/m³;TWA(as respirable

dust):4 mg/m³

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeNitrile rubber.No data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquid.ColourWhite

Specific Physical Form: Slurry Odor Solvent

Odour threshold *No data available.*

pH 8 - 8.5

Boiling point/boiling rangeNo data available.Melting pointNot applicable.Flammability (solid, gas)Not applicable.Explosive propertiesNot classifiedOxidising propertiesNot classified

Flash point > 125 °C [Test Method: Setaflash]

Autoignition temperatureNo data available.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.Vapour pressureNo data available.

Relative density 0.917 - 0.993 [*Ref Std*:WATER=1]

Water solubilityNo data available.Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour densityNo data available.Decomposition temperatureNo data available.

Viscosity 20,000 mPa-s [@ 40 °C] [Test Method: Brookfield]

Density 0.917 - 0.993 g/cm3

9.2. Other information

EU Volatile Organic Compounds 296.9 g/l Percent volatile 31 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

High shear and high temperature conditions

10.5 Incompatible materials

Alkali and alkaline earth metals. Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, $\leq 2\%$ aromatics	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 454 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Minimal irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Rabbit	Mild irritant
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea	Not classified
	pig	
White mineral oil (petroleum)	Guinea	Not classified
	pig	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Guinea	Not classified
	pig	
1,2-benzisothiazol-3(2H)-one	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%	Not	Not	Not carcinogenic
aromatics	specified.	available	
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2%	Not	Not	Not carcinogenic
aromatics	specified.	available	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	premating & during gestation

Hydrocarbons, C12-C15, n-alkanes,	Not	Not classified for male reproduction	Rat	NOAEL Not	28 days
isoalkanes, cyclics, < 2% aromatics	specified.			available	
Hydrocarbons, C12-C15, n-alkanes,	Not	Not classified for male reproduction	Rat	NOAEL Not	1 generation
isoalkanes, cyclics, < 2% aromatics	specified.			available	
Hydrocarbons, C12-C15, n-alkanes,	Not	Not classified for development	Rat	NOAEL Not	during
isoalkanes, cyclics, < 2% aromatics	specified.			available	gestation
Hydrocarbons, C12-C15, n-alkanes,	Not	Not classified for development	Rat	NOAEL Not	1 generation
isoalkanes, cyclics, < 2% aromatics	specified.			available	
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112	2 generation
				mg/kg/day	_
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112	2 generation
		_		mg/kg/day	_
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112	2 generation
, ,	-			mg/kg/day	_

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,2-benzisothiazol-3(2H)- one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	similar health	NOAEL Not available	
			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non- fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	liver hematopoietic system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)- one	Ingestion	heart endocrine system nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure		Test result
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11- C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	No obs Effect Level	1,000 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Experimental	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Rainbow trout	Experimental	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Water flea	Experimental	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Green Algae	Experimental	72 hours	No obs Effect Level	1,000 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l

White mineral oil	8042-47-5	Water flea	Estimated	21 days	No obs Effect	>100 mg/l
(petroleum)					Level	
1,2-benzisothiazol-	2634-33-5	Green algae	Experimental	72 hours	EC50	0.11 mg/l
3(2H)-one						_
1,2-benzisothiazol-	2634-33-5	Pacific oyster	Experimental	48 hours	EC50	0.062 mg/l
3(2H)-one		-				_
1,2-benzisothiazol-	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
3(2H)-one						_
1,2-benzisothiazol-	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
3(2H)-one			•			
1,2-benzisothiazol-	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
3(2H)-one		_	-			_

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Aluminium Oxide (non- fibrous)	1344-28-1	Data not availbl- insufficient			N/A	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Estimated Biodegradation	28 days	BOD	67.6 % BOD/ThBOD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)- one	2634-33-5	Experimental BCF - Bluegill	56 days	Bioaccumulation factor	6.62	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

This product has been classified as a non-hazardous waste. Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

GC-8010-4166-3, GC-8010-4167-1, UU-0016-6331-7, UU-0016-6335-8

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066 Repeated exposure may cause skin dryness or cracking.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.

Revision information:

Professional Use of Cleaner: Section 16: Annex information was deleted.

List of sensitizers information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 5: Hazardous combustion products table information was modified.

Section 8: DNEL table row information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eve Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Sectio 16: UK disclaimer information was deleted.

Annex

1. Title					
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6; Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics; EC No. 920-107-4;				
Exposure Scenario Name	Professional Use of Coatings				
Lifecycle Stage	Widespread use by professional workers				
Contributing activities	PROC 10 -Roller application or brushing				
Contributing activities	ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)				
Processes, tasks and activities covered	Application of product with microfiber towel, cloth, or brush				
2. Operational conditions and risk management measures					
Operating Conditions	Physical state:Liquid. General operating conditions: Duration of exposure per day at workplace [for one worker]: Daily; Emission days per year: 300 days/year; Frequency of exposure at workplace [for one worker]: 8 hours/day; Indoor use; Outdoor use;				
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;				
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;				
3. Prediction of exposure	•				
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.				

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to

satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk