

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 1 / 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. product identifiers**

Article No. (manufacturer/supplier) 205X00  
Trade name/designation Graining Pen  
Art.No. 205000, 205900  
all colours, all gloss values

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Coating (Paint, Varnish).

**Uses advised against:**

Do not use for products which come into contact with the food stuffs.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer/supplier**

Heinrich König GmbH & Co. KG  
An der Rosenhelle 5  
61138 Niederdorfelden  
Germany

Telephone: +49 (0)6101 5360 0  
Telefax: +49 (0)6101 5360 11  
E-mail: [Info@heinrich-koenig.de](mailto:Info@heinrich-koenig.de)  
Website: [www.heinrich-koenig.de](http://www.heinrich-koenig.de)

**Department responsible for information:**

Laboratory

Only available during office hours:

Telephone: +49 (0)6101 5360 71  
Mon - Thurs 08:00 to 16:00  
Friday 08:00 - 12:30

E-mail (competent person)

[SDB@heinrich-koenig.de](mailto:SDB@heinrich-koenig.de)

**1.4. Emergency telephone number**

Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK  
GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves and eye/face protection.  
P370 + P378 In case of fire: Use foam to extinguish.

**Hazard components for labelling**

C.I. Solvent Yellow 88  
1-methoxy-2-propanol  
C.I. Solvent Red 122

**Supplemental hazard information**

not determined

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 2 / 11

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Description** Dye solution

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
203-539-1 107-98-2 603-064-00-3	01-2119457435-35-xxxx 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	50 < 100
200-578-6 64-17-5 603-002-00-5	01-2119457610-43-xxxx Ethanol Eye Irrit. 2 H319 / Flam. Liq. 2 H225	20 < 25
252-104-2 34590-94-8	01-2119450011-60-xxxx (2-methoxymethylethoxy)propanol Substance with a common (EC) occupational exposure limit value.	7 < 10
943-145-3	C.I. Solvent Red 122 Skin Sens. 1B H317 / Aquatic Chronic 3 H412	0,25 < 0,3
287-007-4 85408-46-4	01-2120766190-58-xxxx Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)] chromate(1-) Skin Sens. 1A H317 / Aquatic Chronic 2 H411	0,1 < 0,25
216-455-5 1589-47-5 603-106-00-0	2-methoxypropanol Flam. Liq. 3 H226 / Repr. 1B H360D / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318	0,1 < 0,25

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 3 / 11

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 4 / 11

**SECTION 8: Exposure controls/personal protection**

8.1. **Control parameters**

**Occupational exposure limit values:**

not determined

**DNEL:**

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 283 mg/kg  
DNEL long-term inhalative (systemic), Workers: 308 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 36 mg/kg  
DNEL long-term dermal (systemic), Consumer: 121 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m<sup>3</sup>

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 183 mg/kg  
DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Workers: 553,5 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 33 mg/kg  
DNEL long-term dermal (systemic), Consumer: 78 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

DNEL long-term dermal (systemic), Workers: 343 mg/kg  
DNEL acute inhalative (local), Workers: 1900 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 950 mg/m<sup>3</sup>  
DNEL long-term oral (repeated), Consumer: 87 mg/kg  
DNEL acute dermal, short-term (systemic), Consumer: 950 mg/kg  
DNEL long-term dermal (systemic), Consumer: 206 mg/kg  
DNEL acute inhalative (local), Consumer: 950 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Consumer: 114 mg/m<sup>3</sup>

**PNEC:**

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

PNEC aquatic, freshwater: 19 mg/L  
PNEC aquatic, marine water: 1,9 mg/L  
PNEC aquatic, intermittent release: 190 mg/L  
PNEC sediment, freshwater: 70,2 mg/kg  
PNEC sediment, marine water: 7,02 mg/kg  
PNEC, soil: 2,74 mg/kg  
PNEC sewage treatment plant (STP): 4168 mg/L

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L  
PNEC aquatic, marine water: 1 mg/L  
PNEC aquatic, intermittent release: 100 mg/L  
PNEC sediment, freshwater: 52,3 mg/kg  
PNEC sediment, marine water: 5,2 mg/kg  
PNEC, soil: 4,59 mg/kg  
PNEC sewage treatment plant (STP): 100 mg/L

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

PNEC aquatic, freshwater: 0,96 mg/L  
PNEC aquatic, marine water: 0,79 mg/L  
PNEC aquatic, intermittent release: 2,75 mg/L  
PNEC sediment, freshwater: 3,6 mg/kg  
PNEC sediment, marine water: 2,9 mg/kg

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 5 / 11

PNEC, soil: 0,63 mg/kg  
PNEC sewage treatment plant (STP): 580 mg/L  
PNEC Secondary Poisoning: 0,72 mg/kg

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>refer to label</b>
<b>Odour:</b>	<b>Preparations containing solvent</b>
<b>Odour threshold:</b>	<b>not determined</b>
<b>Melting point/freezing point:</b>	<b>n.a.</b>
<b>Initial boiling point and boiling range:</b>	<b>78 °C</b> Method: calculated. Source: Ethanol
<b>Flammability:</b>	not determined
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>1,94 Vol-%</b> Method: calculated.
<b>Upper explosion limit:</b>	<b>15 Vol-%</b> Method: calculated. Source: Ethanol
<b>Flash point:</b>	<b>12 °C</b> Method: calculated.
<b>Auto-ignition temperature:</b>	<b>270 °C</b> Method: calculated. Source: 1-methoxy-2-propanol
<b>Decomposition temperature:</b>	<b>not determined</b>
<b>pH at 20 °C:</b>	<b>N.A.</b>
<b>Viscosity at 20 °C:</b>	<b>16 s 4 mm</b> Method: DIN 53211

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 6 / 11

**Solubility(ies):**  
**Water solubility at 20 °C:** partially soluble  
**Partition coefficient: n-octanol/water:** see section 12  
**Vapour pressure at 20 °C:** 27,9605 mbar  
Method: calculated.

**Density and/or relative density:**  
**Density at 20 °C:** 0,90 g/cm<sup>3</sup>  
Method: calculated.

**Relative vapour density:** not determined  
**particle characteristics:** not applicable

9.2. **Other information**

**Solid content:** 7,71 weight-%  
**solvent content:**  
**Organic solvents:** 92 weight-%  
**Water:** 0 weight-%

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008** \*

**Acute toxicity**

Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)  
oral, LD50, Rat: > 5000 mg/kg  
inhalative (dust and mist), LC50, Rat: > 9,5 mg/L (4 h)

(2-methoxymethylethoxy)propanol  
oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rabbit: 9510 mg/kg  
inhalative (vapours), LC50, Rat: 3,35 mg/L 3,35 (4 h)  
Based on available data the classification criteria are not met.

1-methoxy-2-propanol  
oral, LD50, Rat: 4016 mg/kg  
dermal, LD50, Rabbit: > 2000 mg/kg  
inhalative (vapours), LC50, Rat: > 25,8 mg/L (4 h)  
Based on available data, the classification criteria are not met.

Ethanol  
oral, LD50, Rat: 10470 mg/kg  
Method: OECD 401  
dermal, LD50, Rabbit: > 2000 mg/kg  
Method: OECD 402  
inhalative (vapours), LC50, Rat: 51 mg/L (4 h)  
Method: OECD 403

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 7 / 11

Based on available data, the classification criteria are not met.

**Skin corrosion/irritation; Serious eye damage/eye irritation**

2-methoxypropanol

Skin (4 h)

Causes skin irritation.

eyes

Causes serious eye damage..

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

C.I. Solvent Red 122

Skin, Mouse:

Method: OECD 429

May cause an allergic skin reaction.

Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)

Skin, Mouse:

Method: OECD 429

May cause an allergic skin reaction.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

2-methoxypropanol

Reproductive toxicity

May damage the unborn child.

**STOT-single exposure; STOT-repeated exposure**

May cause drowsiness or dizziness.

2-methoxypropanol

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall assessment on CMR properties**

EC No. CAS No.	Designation	Classification according to Regulation (EC) No 1272/2008 [CLP]
216-455-5 1589-47-5	2-methoxypropanol	Repr. 1B

11.2. **Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. **Toxicity**

Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)

Fish toxicity, LC50, Danio rerio (zebrafish) 1 - 10 mg/L (96 h)

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 8 / 11

Toxic to aquatic life.; Technically correct releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge.

Daphnia toxicity, EC50 (48 h)  
not determined

Algae toxicity, ErC50  
not determined

Activated sludge, EC50: > 100 mg/L (3 h)

(2-methoxymethylethoxy)propanol

Fish toxicity, LC50, Poecilia reticulata (Guppy): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 969 mg/L (96 h)

Method: OECD 201

Bacteria toxicity, EC10, Pseudomonas putida: 4168 mg/L (18 h)

Based on available data the classification criteria are not met.

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/L (96 h)

Based on available data, the classification criteria are not met.

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 21100 - 25900 mg/L (48 h)

Based on available data, the classification criteria are not met.

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h); Evaluation Inhibition of growth rate.

Method: OECD 201

Ethanol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 15300 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 12340 mg/L (48 h)

Algae toxicity, ErC50, Chlorella vulgaris: 275 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, EC50, Pseudomonas putida: 5800 mg/L (4 h)

Based on available data, the classification criteria are not met.

### Long-term Ecotoxicity

C.I. Solvent Red 122

Fish toxicity, LC50 (96 h)

Harmful to aquatic life with long lasting effects.

Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)

Fish toxicity, LC50 (96 h)

Toxic to aquatic life with long lasting effects.

(2-methoxymethylethoxy)propanol

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): > 0,5 mg/L (22 D)

Based on available data the classification criteria are not met.

1-methoxy-2-propanol

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h)

Based on available data, the classification criteria are not met.

### 12.2. Persistence and degradability

(2-methoxymethylethoxy)propanol

Biodegradation: 75 % (28 D)

Method: OECD 301 F

Readily biodegradable (according to OECD criteria).

1-methoxy-2-propanol

Biodegradation: 96 % (28 d)

Method: OECD 301E

Readily biodegradable (according to OECD criteria).

Ethanol

Biodegradation, aerobic.: 97 % (28 D)

Readily biodegradable (according to OECD criteria).

### 12.3. Bioaccumulative potential

(2-methoxymethylethoxy)propanol



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00                      Graining Pen  
Print date: 07.03.2023                Revision date: 14.07.2022  
Version: 2.0                                Issue date: 02.08.2021

GB  
Page 9 / 11

Partition coefficient: n-octanol/water: 0,006

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: 0,37

Ethanol

Partition coefficient: n-octanol/water: -0,35

**Bioconcentration factor (BCF)**

(2-methoxymethylethoxy)propanol

Bioconcentration factor (BCF): < 100

Ethanol

Bioconcentration factor (BCF): 0,66

No indication of bioaccumulation potential.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product**

**Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\*                      Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number or ID number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

II

**14.5. Environmental hazards**

Land transport (ADR/RID)

not determined

Marine pollutant

not determined

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.: 205X00  
 Print date: 07.03.2023  
 Version: 2.0

Graining Pen  
 Revision date: 14.07.2022  
 Issue date: 02.08.2021

GB  
 Page 10 / 11

Tunnel restriction code D/E  
 SPECIAL PROVISIONS 640D

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

Maximum VOC content of the product in a ready to use condition (in g/L): 830

**Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**

VOC product category: (Cat. B/e) ; VOC limit value: 840 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 830

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**Substance/product listed in the following inventories:**

DSL listed  
 TSCA listed

**REACH candidate list of substances of very high concern (SVHC) for the approval process.**

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

**Regulation (EC) 1907/2006. material in question applies. Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)**

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

**15.2. Chemical Safety Assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35-xxxx
200-578-6 64-17-5	Ethanol	01-2119457610-43-xxxx
252-104-2 34590-94-8	(2-methoxymethylethoxy)propanol	01-2119450011-60-xxxx
287-007-4 85408-46-4	Amines, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)	C12-14-tert-alkyl, 01-2120766190-58-xxxx

**SECTION 16: Other information**

**Full text of classification in section 3**

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Sens. 1B / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Repr. 1B / H360D	Reproductive toxicity	May damage the unborn child.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 205X00  
Print date: 07.03.2023  
Version: 2.0

Graining Pen  
Revision date: 14.07.2022  
Issue date: 02.08.2021

GB  
Page 11 / 11

Skin Irrit. 2 / H315      Skin corrosion/irritation      Causes skin irritation.  
Eye Dam. 1 / H318      Serious eye damage/eye irritation      Causes serious eye damage.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2      Flammable liquids      On basis of test data.  
Skin Sens. 1      Respiratory or skin sensitisation      Calculation method.  
STOT SE 3      STOT-single exposure      Calculation method.

**Abbreviations and acronyms**

ADR      European Agreement concerning the International Carriage of Dangerous Goods by Road  
OEL      Occupational Exposure Limit Value  
BLV      Biological Limit Value  
CAS      Chemical Abstracts Service  
CLP      Classification, Labelling and Packaging  
CMR      Carcinogenic, Mutagenic and Reprotoxic  
DIN      German Institute for Standardization / German industrial standard  
DNEL      Derived No-Effect Level  
EAKV      European Waste Catalogue Directive  
EC      Effective Concentration  
EC      European Community  
EN      European Standard  
IATA-DGR      International Air Transport Association – Dangerous Goods Regulations  
IBC Code      International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ICAO-TI      International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG Code      International Maritime Code for Dangerous Goods  
ISO      International Organization for Standardization  
LC      Lethal Concentration  
LD      Lethal Dose  
MARPOL      Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD      Organisation for Economic Cooperation and Development  
PBT      persistent, bioaccumulative, toxic  
PNEC      Predicted No Effect Concentration  
REACH      Registration, Evaluation, Authorisation and Restriction of Chemicals  
RID      Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN      United Nations  
VOC      Volatile Organic Compounds  
vPvB      very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.

\* Data changed compared with the previous version