according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 215000 Colour Concentrate
Print date: 01.12.2023 Revision date: 28.11.2023
Version: 1.21 Issue date: 28.11.2023

GB Page 1 / 9



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 215000

Trade name/designation Colour Concentrate

UFI: VASA-KVWV-W20X-7E3D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Coating (Paint, Varnish).

Uses advised against:

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier

Heinrich König GmbH & Co. KG

An der Rosenhelle 5
Telephone: +49 (0)6101 5360 0
61138 Niederdorfelden
Telefax: +49 (0)6101 5360 11
Germany
E-mail: Info@heinrich-koenig.de
Website: www.heinrich-koenig.de

Department responsible for information:

Laboratory Telephone: +49 (0)6101 5360 71 Only available during office hours: Mon - Thurs 08:00 to 16:00

Friday 08:00 - 12:30

E-mail (competent person) SDB@heinrich-koenig.de

1.4. Emergency telephone number

Emergency telephone number Emergency CONTACT (24-Hour-Number): GBK

GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Warning

Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378 In case of fire: Use foam to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

1-methoxy-2-propanol

Supplemental hazard information

not determined

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 215000 Colour Concentrate
Print date: 01.12.2023 Revision date: 28.11.2023
Version: 1.21 Issue date: 28.11.2023

GB Page 2 / 9



3.2. Mixtures

Description Dye solution

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
203-539-1 107-98-2 603-064-00-3	01-2119457435-35-xxxx 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	50 < 100
216-455-5 1589-47-5 603-106-00-0	2-methoxypropanol Flam. Liq. 3 H226 / Repr. 1B H360D / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318	0,1 < 0,25

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

according to Regulation (EU) 2020/878

Article No.: 215000 Colour Concentrate
Print date: 01.12.2023 Revision date: 28.11.2023
Version: 1.21 Issue date: 28.11.2023



Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent

GB

6.3. Methods and material for containment and cleaning up

authorities in accordance with local regulations.

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not determined

DNEL:

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 183 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m³

DNEL acute inhalative (systemic), Workers: 553,5 mg/m³

DNEL long-term inhalative (systemic), Workers: 369 mg/m³

DNEL long-term oral (repeated), Consumer: 33 mg/kg

DNEL long-term dermal (systemic), Consumer: 78 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m³

PNEC:

1-methoxy-2-propanol

Index No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

215000 Colour Concentrate Article No.: Revision date: 28.11.2023 Print date: 01.12.2023 Issue date: 28.11.2023 Version:

PNEC aquatic, freshwater: 10 mg/L

PNEC aquatic, intermittent release: 100 mg/L PNEC sediment, freshwater: 52,3 mg/kg PNEC sediment, marine water: 5,2 mg/kg

PNEC aquatic, marine water: 1 mg/L

PNEC, soil: 4,59 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: refer to label

Odour. **Preparations containing solvent**

Odour threshold: not determined

Melting point/freezing point: n.a. Initial boiling point and boiling range: 120 °C

Method: calculated.

Source: 1-methoxy-2-propanol Flammable liquid and vapour.

Lower and upper explosion limit:

Flammability:

Lower explosion limit: 1,5 Vol-%

Method: calculated.

Upper explosion limit: 13,7 Vol-%

Method: calculated.

Source: 1-methoxy-2-propanol

Flash point: 32 °C

Method: calculated.

270 °C **Auto-ignition temperature:**

Method: calculated.

Source: 1-methoxy-2-propanol

not determined **Decomposition temperature:**



GB

Page 4 / 9

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 215000 Colour Concentrate
Print date: 01.12.2023 Revision date: 28.11.2023
Version: 1.21 Issue date: 28.11.2023

GB Page 5 / 9



pH at 20 °C: not applicable Kinematic viscosity (20°C) < 7 mm²/s

Viscosity at 20 °C: 25 s 3 mm

Method: EN ISO 2431

Solubility(ies):

Water solubility at 20 °C: miscible
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: 10,4542 mbar
Method: calculated.

Density and/or relative density:

Relative vapour density:

particle characteristics:

Density at 20 °C: 0,94 g/cm³

Method: calculated.
not determined

not applicable

9.2. Other information

Solid content: 9,10 weight-%

solvent content:

Organic solvents: 91 weight-% Water: 0 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: > 25,8 mg/L (4 h)

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

2-methoxypropanol

Skin (4 h)

Causes skin irritation.

eves

Causes serious eye damage..

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

215000 Colour Concentrate Article No.: Revision date: 28.11.2023 Print date: 01.12.2023 Issue date: 28.11.2023 Version:

GB Page 6 / 9



CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

2-methoxypropanol

Reproductive toxicity

May damage the unborn child.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

2-methoxypropanol

Specific target organ toxicity (single exposure), Irritation

May cause respiratory irritation.

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

EC No. CAS No.	Designation	Classification according to Regulation (EC) No 1272/2008
216-455-5 1589-47-5	2-methoxypropanol	[CLP] Repr. 1B

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/L (96 h)

Based on available data, the classification criteria are not met.

Daphnia toxicity, EC50, Daphnia magna (Big water flea) 21100 - 25900 mg/L (48 h)

Based on available data, the classification criteria are not met.

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h); Evaluation Inhibition of growth rate.

Method: OECD 201 Long-term Ecotoxicity

1-methoxy-2-propanol

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h)

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

1-methoxy-2-propanol

Biodegradation: 96 % (28 d)

Method: OECD 301E

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

1-methoxy-2-propanol

Partition coefficient: n-octanol/water: 0,37

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

215000 Colour Concentrate Article No.: Revision date: 28.11.2023 Print date: 01.12.2023 Issue date: 28.11.2023 Version:

GB Page 7 / 9



12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint Sea transport (IMDG): **PAINT** Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) not determined not determined Marine pollutant

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 215000 Colour Concentrate Revision date: 28.11.2023 Print date: 01.12.2023 Issue date: 28.11.2023 Version:

GB Page 8 / 9



Maximum VOC content of the product in a ready to use condition (in g/L): 864

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

DSL listed TSCA listed

REACH candidate list of substances of very high concern (SVHC) for the approval process.

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

Regulation (EC) 1907/2006. material in question applies.Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No.	Designation	REACH No.
CAS No.		
203-539-1	1-methoxy-2-propanol	01-2119457435-35-xxxx
107-98-2	,	

SECTION 16: Other information

Full text of classification in section 3

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour. STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness. Reproductive toxicity May damage the unborn child. Repr. 1B / H360D STOT SE 3 / H335 May cause respiratory irritation. STOT-single exposure Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation. Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] Flam. Liq. 3 Flammable liquids On basis of test data. STOT SE 3 STOT-single exposure Calculation method.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

BLV Biological Limit Value CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging Carcinogenic, Mutagenic and Reprotoxic **CMR**

DIN German Institute for Standardization / German industrial standard

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC **Effective Concentration** EC **European Community** ΕN European Standard

IATA-DGR International Air Transport Association - Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

International Maritime Code for Dangerous Goods **IMDG Code** ISO International Organization for Standardization

LC Lethal Concentration

Lethal Dose LD

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Seit 189

GB Page 9 / 9

Article No.: 215000 Colour Concentrate
Print date: 01.12.2023 Revision date: 28.11.2023
Version: 1.21 Issue date: 28.11.2023

PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN United Nations

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.

* Data changed compared with the previous version