according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 GB Version: 2.3 Revision date: 10.01.2024 Page 1 / 10



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 506000
Trade name/designation Plastic Cleaner

UFI: EYXA-0VG3-420K-WXJN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier

Heinrich König GmbH & Co. KG

An der Rosenhelle 5

61138 Niederdorfelden

Germany

Telephone: +49 (0)6101 5360 0

Telefax: +49 (0)6101 5360 11

E-mail: Info@heinrich-koenig.de

Website: www.heinrich-koenig.de

Department responsible for information:

Laboratory

Telephone: +49 (0)6101 5360 71

Only available during office hours:

Mon - Thurs 08:00 to 16:00

Friday 08:00 - 12:30

E-mail (competent person) SDB@heinrich-koenig.de

1.4. Emergency telephone number

Emergency telephone number Emergency CONTACT (24-Hour-Number): GBK

GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225 Flammable liquids Highly flammable liquid and vapour. Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation. STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness.

Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways. Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms









Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use foam to extinguish.

P391 Collect spillage.

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazard components for labelling

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cle

Article No.: 506000 Plastic Cleaner
Print date: 10.01.2024 Revision date: 10.01.2024
Version: 2.3 Plastic Cleaner
Revision date: 10.01.2024
Issue date: 04.01.2024

Revision date: 10.01.2024 GB Issue date: 04.01.2024 Page 2 / 10



Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Cleaner, solvent-based

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification // Remark	weight-%
920-750-0	01-2119473851-33-xxxx Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%) STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 2 H225 / EUH066	25 < 50
200-578-6 64-17-5 603-002-00-5	01-2119457610-43-xxxx Ethanol Eye Irrit. 2 H319 / Flam. Liq. 2 H225	25 < 50

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 Version: 2.3 Revision date: 04.01.2024



GB

Page 3 / 10

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not determined

DNEL:

Ethanol


Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5 DNEL long-term dermal (systemic), Workers: 343 mg/kg DNEL acute inhalative (local), Workers: 1900 mg/m³

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

506000 Plastic Cleaner Article No.:

Print date: 10.01.2024 Revision date: 10.01.2024 GB Issue date: 04.01.2024 Page 4 / 10 Version:



DNEL long-term oral (repeated), Consumer: 87 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 950 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg DNEL acute inhalative (local), Consumer: 950 mg/m³

DNEL long-term inhalative (systemic), Consumer: 114 mg/m³

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0.1%)

EC No. 920-750-0

DNEL long-term dermal (systemic), Workers: 773 mg/kg DNEL long-term inhalative (systemic), Workers: 2035 mg/m³ DNEL long-term oral (repeated), Consumer: 699 mg/kg DNEL long-term dermal (systemic), Consumer: 699 mg/kg DNEL long-term inhalative (systemic), Consumer: 608 mg/m³

PNEC:

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

PNEC aquatic, freshwater: 0,96 mg/L PNEC aquatic, marine water: 0,79 mg/L PNEC aquatic, intermittent release: 2,75 mg/L PNEC sediment, freshwater: 3,6 mg/kg PNEC sediment, marine water: 2,9 mg/kg

PNEC, soil: 0,63 mg/kg

PNEC sewage treatment plant (STP): 580 mg/L PNEC Secondary Poisoning: 0,72 mg/kg

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: Greenish

Odour: Preparations containing solvent

Odour threshold: not determined

Melting point/freezing point: n.a. Initial boiling point and boiling range: 78 °C



according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

according to Negalation (LO) 2020/076

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 GB Version: 2.3 Revision date: 10.01.2024 Page 5 / 10

Method: calculated.

Flammability: Highly flammable liquid and vapour.

Lower and upper explosion limit:

Lower explosion limit: 3,47 Vol-%

Method: calculated.

Source: Ethanol

Upper explosion limit: 15 Vol-%

Method: calculated. Source: Ethanol

Flash point: -2 °C

Method: calculated.

Auto-ignition temperature: 260 °C

Method: calculated.

Source: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of

Benzene <0,1%)

Decomposition temperature: not determined

pH at 20 °C: not applicable Kinematic viscosity (20°C) < 7 mm²/s

Viscosity at 20 °C: 22 s 3 mm

Method: EN ISO 2431

Solubility(ies):

Water solubility at 20 °C: partially soluble
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: 52,9483 mbar
Method: calculated.

Density and/or relative density:

Relative vapour density:

particle characteristics:

Density at 20 °C: 0,76 g/cm³

Method: calculated. not determined not applicable

9.2. Other information

Solid content: 0,00 weight-%

solvent content:

Organic solvents: 100 weight-% Water: 0 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.



according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 Version: 2.3 Revision date: 04.01.2024



GB

Page 6 / 10

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Ethanol

oral, LD50, Rat: 10470 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 51 mg/L (4 h)

Method: OECD 403

Based on available data, the classification criteria are not met.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Specific target organ toxicity (single exposure), drowsiness

May cause drowsiness or dizziness.

Aspiration hazard

May be fatal if swallowed and enters airways.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Ethanol

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

 Print date:
 10.01.2024
 Revision date: 10.01.2024
 GB

 Version:
 2.3
 Issue date: 04.01.2024
 Page 7 / 10

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 15300 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 12340 mg/L (48 h)

Algae toxicity, ErC50, Chlorella vulgaris: 275 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, EC50, Pseudomonas putida: 5800 mg/L (4 h) Based on available data, the classification criteria are not met.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%) Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout) 3 - 10 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea) 4,6 - 10 mg/L (48 h) Algae toxicity, ErC50, Pseudokirchneriella subcapitata 10 - 30 mg/L (72 h)

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Fish toxicity, LC50 (96 h)

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Ethanol

Biodegradation, aerobic.: 97 % (28 D)

Readily biodegradable (according to OECD criteria).

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Biodegradation:

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

Ethanol

Partition coefficient: n-octanol/water: -0,35

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Partition coefficient: n-octanol/water: 4 - 5,7 No indication of bioaccumulation potential.

Bioconcentration factor (BCF)

Ethanol

Bioconcentration factor (BCF): 0,66 No indication of bioaccumulation potential.

12.4. Mobility in soil

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)

Product is easily volatile.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package



according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 Version: 2.3 Revision date: 10.01.2024 Issue date: 04.01.2024



Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

Sea transport (IMDG):

Land transport (ADR/RID): Flammable liquid, n.o.s.

(HYDROCARBONS MIXTURE) FLAMMABLE LIQUID, N.O.S.

(HYDROCARBONS MIXTURE, Hydrocarbons, C7-C9, n-alkanes,

GB

Page 8 / 10

isoalkanes, cyclics, (Content of Benzene <0,1%))

Air transport (ICAO-TI / IATA-DGR): Flammable liquid, n.o.s.

(HYDROCARBONS MIXTURE)

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) ENVIROMENTALLY HAZARDOUS

Marine pollutant p / Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of

Benzene <0,1%)

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Maximum VOC content of the product in a ready to use condition (in g/L): 758

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

DSL listed

TSCA listed

REACH candidate list of substances of very high concern (SVHC) for the approval process.

According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.

Regulation (EC) 1907/2006. material in question applies.Regulation (EC) 1907/2006 (REACH) Annex XIV (list of substances subject to authorization)

According to the available data and / or according to the information provided by the suppliers, the product does not contain

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024
Version: 2.3 Revision date: 04.01.2024

GB Page 9 / 10



any substance that is considered to be a substance that requires authorization according to REACH Regulation (EC) 1907/2006 Annex XIV.

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, (Content of Benzene <0,1%)	f 01-2119473851-33-xxxx
200-578-6 64-17-5	Ethanol	01-2119457610-43-xxxx

SECTION 16: Other information

Full text of classification in section 3

STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness.

Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways. Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

Flam. Liq. 2 / H225 Flammable liquids Highly flammable liquid and vapour.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 Flammable liquids On basis of test data.

Eye Irrit. 2 Serious eye damage/eye irritation Calculation method.

STOT SE 3 STOT-single exposure Calculation method.

Asp. Tox. 1 Aspiration hazard Calculation method.

Aquatic Chronic 2 Hazardous to the aquatic environment Calculation method.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

BLV Biological Limit Value
CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DIN German Institute for Standardization / German industrial standard

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC Effective Concentration
EC European Community
EN European Standard

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN United Nations

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 506000 Plastic Cleaner

Print date: 10.01.2024 Revision date: 10.01.2024 Version: 2.3 Revision date: 04.01.2024

GB Page 10 / 10



section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

You can also find current SDSs for our standard products online on our homepage under **Downloads** in the relevant product area.

* Data changed compared with the previous version