

Article Print c Versio	late:	655500 23.01.202 3.0	24	Sanding Liquid Revision date: 23 Issue date: 19.01		GB Page 1 / 8	Seit 1892	
SEC	TION 1: Ide	entificatio	on of the	substance/mixt	ture and of the c	ompany/undertaking		
1.1.	Product id	entifier						
	Article No. Trade nam			ər)	655500 Sanding Liquid UFI: VM0C-MVł	<m-y200-femv< td=""><td></td></m-y200-femv<>		
1.2.	Relevant i	dentified u	ses of the	substance or m	ixture and uses ad	dvised against		
1.3.	Relevant identified uses Product for surface repair and surface polish.							
	Details of the supplier of the safety data shee Manufacturer/supplier Heinrich König GmbH & Co. KG An der Rosenhelle 5 61138 Niederdorfelden Germany				Telephone: +49 (0)6101 5360 0 Telefax: +49 (0)6101 5360 11 E-mail: Info@heinrich-koenig.de Website: www.heinrich-koenig.de			
	Departmer Laboratory Only availa	-			Telephone: +49 Mon - Thurs 08: Friday 08:00 - 1			
	E-mail (cor	npetent per	son)		SDB@heinrich-	koenig.de		
1.4.	Emergenc	y telephon	e number			-		
	Emergency	telephone	number		Emergency COl GmbH +49 (0)6	NTACT (24-Hour-Number 132-84463	): GBK	
SEC	TION 2: Ha	zarde ide	ntificatio	'n				
2.1.				e or mixture			*	
2.1.					1272/2008 [CLP]			
			-			lo 1272/2008 [CLP].		
	Flam. Liq. 2			Flammable liquids			e liquid and vapour.	
2.2.	Label elem					r ngrny narinnabie	*	
	Labelling a	according	to Regula	tion (EC) No. 127	2/2008 [CLP]			
	Hazard pic	tograms						
		Danger	r					
	Hazard sta H225	tements	Highly fla	mmable liquid and	l vapour.			
	<b>Precaution</b> P210 P370 + P37 P403 + P23	78	Keep awa In case o	ay from heat, hot s <sup>;</sup> fire: Use foam to well-ventilated pla	extinguish.	pen flames and other ignit	ion sources. No smoking.	
	Hazard co	mponents	for labelli not deter					
	Suppleme	ntal hazaro	<b>informa</b> t not deter					
2.3.	Other haza No informa		ole.					
SEC	TION 3: Co	mpositio	n/inform	ation on ingred	lients			
3.2.	Mixtures							
0.2.	Deserintia		Solvent /					

Description Solvent / thinner

Classification according to Regulation (EC) No 1272/2008 [CLP]



Article No.: Print date: Version:	655500 23.01.2024 3.0	Sanding Liquid Revision date: 23.01.2024 Issue date: 19.01.2024	GB Page 2 / 8	Seit 1892	
EC No. CAS No Index N	). Desig	CH No. gnation ification // Remark		weight-%	
200-578 64-17-5 603-002	Ethar	19457610-43-xxxx nol . Liq. 2 H225		50 < 100	

#### **Additional information**

Full text of classification: see section 16

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

# In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

# 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

# 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

# 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

## 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

		®
Seit	1892	

Article No.:	655500	Sanding Liquid
Print date:	23.01.2024	Revision date: 23.01.2024
Version:	3.0	Issue date: 19.01.2024

GB Page 3 / 8

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

# Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

# **Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

## Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## Occupational exposure limit values:

not determined

## DNEL:

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

DNEL long-term dermal (systemic), Workers: 343 mg/kg

DNEL acute inhalative (local), Workers: 1900 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 950 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 87 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 950 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg

DNEL acute inhalative (local), Consumer: 950 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Consumer: 114 mg/m<sup>3</sup>

# PNEC:

Ethanol

Index No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

PNEC aquatic, freshwater: 0,96 mg/L

PNEC aquatic, marine water: 0,79 mg/L

PNEC aquatic, intermittent release: 2,75 mg/L

PNEC sediment, freshwater: 3,6 mg/kg

PNEC sediment, marine water: 2,9 mg/kg

PNEC, soil: 0,63 mg/kg

PNEC sewage treatment plant (STP): 580 mg/L

PNEC Secondary Poisoning: 0,72 mg/kg



Article No.: Print date: Version:	655500 23.01.2024 3.0	Sanding Liquid Revision date: 23.01.2024 Issue date: 19.01.2024	GB Page 4 / 8	Seit 189
version.	5.0	15500 Udie. 15.01.2024	raye + / 0	

# 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

# Personal protection equipment

# **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used.

## Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) Thickness of the glove material > 0.4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid colourless
Odour:	Preparations containing solvent
Odour threshold:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	<b>78 °C</b> Method: calculated. Source: Ethanol
Flammability	Highly flammable liquid and vapour.
Lower and upper explosion limit: Lower explosion limit: Upper explosion limit:	<b>3,47 Vol-%</b> Method: calculated. <b>15 Vol-%</b> Method: calculated. Source: Ethanol
Flash point:	22 °C Method: EN ISO 2719
Auto-ignition temperature:	<b>425 °C</b> Method: calculated. Source: Ethanol
Decomposition temperature:	not determined
pH at 20 °C: Cinematic viscosity (40°C):	not applicable < 7 mm²/s
Viscosity at 20 °C: Solubility(ies):	<b>20 s 3 mm</b> Method: EN ISO 2431



Article Print da Versior	ate:	655500 23.01.2024 3.0	Sanding Liq Revision da Issue date:	te: 23.01.2024	GB Page 5 / 8	Seit 1892
	Water so	olubility at 20 °C:		miscible		
		coefficient: n-octa	nol/water:	see section 12		
	Vapour p	pressure at 20 °C:		67,0335 mbar Method: calculate	ed.	
		and/or relative den at 20 °C:	sity:	<b>0,84 g/cm³</b> Method: calculate	ed.	
	Relative	vapour density:		not determined		
	particle of	characteristics:		not applicable		
9.2.	Other inf	ormation				
	Solid cor	ntent:		0,00 weight-%		
	solvent o Organio Water:	content: c solvents:		70 weight-% 30 weight-%		
SECT	<b>FION 10</b> :	Stability and rea	ctivity			
	Reactivit	<b>y</b> nation available.				
			commended reg	ulations for storage an	d handling. Further informat	ion on correct storage: refer to
10.3.		ty of hazardous re ay from strong acids		and strong oxidizing ag	ents to avoid exothermic rea	actions.
-	Stable wh				d handling. Further informati osure to high temperatures.	ion on correct storage: refer to
	Incompa not applic	<b>tible materials</b> cable				
	Hazardou	us decomposition us decomposition by itrogen oxides.	•	orm with exposure to I	nigh temperatures, e.g.: carb	oon dioxide, carbon monoxide,
SECT	<b>FION 11:</b>	Toxicological in	formation			
11.1.		ion on hazard clas		in Regulation (EC) No	o 1272/2008	
	oral, LD Method: dermal, Method: inhalativ Method:	50, Rat: 10470 mg/ : OECD 401 LD50, Rabbit: > 20 : OECD 402 ve (vapours), LC50, : OECD 403 on available data, th	00 mg/kg Rat: 51 mg/L	. ,		
	Skin cor	rosion/irritation; Se	erious eye dam	age/eye irritation		
	Based on	available data, the	classification cr	iteria are not met.		
	Respirat	ory or skin sensitis	sation			
	Based or	available data, the	classification cr	iteria are not met.		
	CMR effe	ects (carcinogenici	ty, mutagenicit	y and toxicity for rep	roduction)	
	Based or	available data, the	classification cr	iteria are not met.		
	STOT-sir	ngle exposure; ST	DT-repeated ex	posure		

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



Article No.: Print date: Version:	655500 23.01.2024 3.0	Sanding Liquid Revision date: 23.01.2024 Issue date: 19.01.2024	GB Page 6 / 8	Seit
VC15I011.	0.0	15500 0010. 15.01.2024	r uge 070	

# Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

# **Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### 11.2. Information on other hazards

## Endocrine disrupting properties

No information available.

# **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

## 12.1. Toxicity

Ethanol Fish toxicity, LC50, Pimephales promelas (fathead minnow): 15300 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 12340 mg/L (48 h) Algae toxicity, ErC50, Chlorella vulgaris: 275 mg/L (72 h) Method: OECD 201 Bacteria toxicity, EC50, Pseudomonas putida: 5800 mg/L (4 h) Based on available data, the classification criteria are not met.

#### Long-term Ecotoxicity

Toxicological data are not available.

# 12.2. Persistence and degradability

#### Ethanol

Biodegradation, aerobic.: 97 % (28 D) Readily biodegradable (according to OECD criteria).

# 12.3. Bioaccumulative potential

Ethanol

Partition coefficient: n-octanol/water: -0,35

## **Bioconcentration factor (BCF)**

Ethanol

Bioconcentration factor (BCF): 0,66 No indication of bioaccumulation potential.

## 12.4. Mobility in soil

Toxicological data are not available.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

# 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

# Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC 140603\*

other solvents and solvent mixtures



Article Print c Versio	date:	655500 23.01.2024 3.0	Sanding Liquid Revision date: 23.01.2024 Issue date: 19.01.2024	GB Page 7 / 8	Seit 1892				
*Hazardous waste according to Directive 2008/98/EC (waste framework directive). Appropriate disposal / Package									
	Recomm Non-conta		may be recycled. Vessels not prop	erly emptied are special waste.					
SEC	TION 14:	Transport inform	ation						
14.1.	UN numb	er or ID number	UN 1170						
14.2.	Land trans	r shipping name sport (ADR/RID): port (IMDG): prt (ICAO-TI / IATA-		LUTION (ETHYL ALCOHOL SO	DLUTION )				
14.3.	Transpor	t hazard class(es)	3						
14.4.	Packing (	group	П						
14.5.	Environm	ental hazards							
	Land tran	sport (ADR/RID)	not determined	b					
	Marine po	llutant	not determine	b					
14.6.	Transport case of ar	Special precautions for user Fransport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8							
	Further information								
	Land trar	sport (ADR/RID)							
		striction code	D/E						
	Sea trans	port (IMDG)							
	EmS-No.	port (	F-E, S-E						
14.7.		transport in bulk a	ccording to IMO instruments						
		ort as bulk accordin	-						
SEC	TION 15:	Regulatory infor	mation						
15.1.	EU legisl Directive	ation 2010/75/EU on ind	ental regulations/legislation spe ustrial emissions [Industrial Emi		ture				
		e (in g/L): 590							
		regulations							
	Observe applicable Observe	<b>Restrictions of occupation</b> Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.							
	According any subst	<b>REACH candidate list of substances of very high concern (SVHC) for the approval process.</b> According to the available data and / or according to the information provided by the suppliers, the product does not contain any substance that is eligible for inclusion in Annex XIV (list of substances subject to authorization) in accordance with Article 57 in conjunction with Article 59 of REACH.							
	substance According any subs	es subject to auth to the available da	. material in question applies. prization) ta and / or according to the inform dered to be a substance that re	ation provided by the suppliers,	the product does not contain				
15.2.		Safety Assessme	nt es of this mixture a chemical safe	ety assessment has been carri	ied out:				



Article No.: Print date: Version:	655500 23.01.202 3.0	Sanding Liqui 24 Revision date Issue date: 19	: 23.01.2024	GB Page 8 / 8	Seit 1892				
EC No.		Designation			REACH No.				
CAS No. 200-578-0	6	Ethanol			01-2119457610-43-xxxx				
64-17-5	0	Ethanor							
<b>SECTION 16:</b>	Other infor	mation							
		tion in section 3:							
	. 2 / H225	Flammable liq	uids	Highly flamma	ble liquid and vapour.				
-	ation proced	-		i iigiii) iidiiiii					
	•	ires and used evaluatior	a method according to	regulation (EC) No 127					
Flam. Liq		Flammable liq		On basis of te					
		•	uluo						
	Abbreviations and acronyms ADR European Agreement concerning the International Carriage of Dangerous Goods by Road								
ADR OEL				onal Camage of Dange	erous Goods by Road				
BLV		Occupational Exposure Limit Value							
CAS		Biological Limit Value Chemical Abstracts Service							
CLP		Classification, Labelling and Packaging							
CMR		Classification, Labelling and Packaging Carcinogenic, Mutagenic and Reprotoxic							
DIN	German Institute for Standardization / German industrial standard								
DNEL		Derived No-Effect Level							
EAKV		European Waste Catalogue Directive							
EC		Effective Concentration							
EC		European Community							
EN		European Standard							
IATA-DG	R	International Air Transport Association – Dangerous Goods Regulations							
IBC Code					ying Dangerous Chemicals in Bulk				
ICAO-TI		International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous							
		Goods by Air	Ū						
IMDG Co	de	International Maritime C	Code for Dangerous Go	oods					
ISO		International Organizati	on for Standardization						
LC		Lethal Concentration							
LD	D Lethal Dose								
MARPOL		Maritime Pollution: The			f Pollution from Ships				
OECD		Organisation for Econor		Development					
PBT		persistent, bioaccumula							
PNEC									
REACH		Registration, Evaluation							
RID		Regulations concerning	the International Carri	iage of Dangerous Goo	ods by Rail				
UN		United Nations							
VOC		Volatile Organic Compo	ounds						

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

## **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version